

ELECTRIC FAN HEATER

TR 9C



FUNCTIONING PRINCIPLES



The device works on the principle of forced convection. The TR are designed to be fixed to the wall. The air flow is forced fan. Cold air is drawn in the back of the unit. Further, it flows from the heater, receives heat. The heated air is expelled in front of the heater. The device has a thermostat for the regulation of temperatures 5-35 °C. The unit area is equipped with thermal protection, which acts automatically. The unit features: ventilation, heating with half the power, heating at full power. The device has a cooling thermostat.

TECHNICAL DATA

Max capacity	kW	9	Power supply	V	380-400	
	Kcal/h	7700		Frequency	Hz	50
	Btu/h	30500			Rated current	A
Combustible	Power		Class of protection	IP24		
Net weight	kg	8,5				
Gross weight	kg	11,2				
Noisy level	dBa	58				
Air displacement	m ³ /h	670				

PACKING

Dimensions packing	mm	410x380x460
Dimensions utilization	mm	335x280x385
Pieces for Euro-pallet	n°	24
Pieces per truck 80m ³	n°	792

COMPONENTS

Heating elements	3000W
Thermostat	With capillary
Fan	∅ 250mm
Thermal protection	85°C
Relay	25A - 14A
Motor	Asynchronous, three-phase, with thermal protection, counterclockwise rotation, 1300rpm

ACCESSORIES

WIRING DIAGRAM

